



Radial shaft seal Simmerring® PPS




DESCRIPTION

- With tension spring
- Rubberized outer jacket
- With protective lip
- Shortened sealing lip
- Sealing material: FKM
- Material reinforcement sheet: unalloyed steel DIN EN 10027-1
- Material tension spring: spring steel DIN EN 10270-1

FUNCTION

- Dynamic sealing of a rotating shaft, independent of the direction of rotation
- Self-retaining
- Good static seal between sealing lip and shaft at standstill
- Rubberized outer jacket ensures tight fit and seal to housing bore
- Protective lip against dirt accumulation from outside
- Shortened sealing lip allows higher operating pressure
- Stronger friction can lead to temperature increase



PRODUCT ADVANTAGES

- Very good static sealing effect with low-viscosity or gaseous media.
- Compensation of thermal expansion e.g. in light metal housings, very good sealing effect with greater roughness and split housings
- Use at high speeds
- Low friction (up to 50% lower frictional torque than commercially available seals)
- Highest quality
- Highest functional reliability
- Longest service life
- No support ring required

APPLICATIONS

- Hydrostatic drives

APPLICATION LIMITS

- Permissible maximum values depending on the other operating conditions, see technical manual.

MEDIA RESISTANCE

- Hydraulic oils ISO VG 68 ** Can only be used for flame-retardant and biodegradable hydraulic fluids after individual testing.
- Please refer to additional information in the chemical resistance guide at www.fst.com.

CONFORMITY AND CERTIFICATES

- Please consult the material data sheet valid for the respective material for current information on approvals and certificates, as this information depends on the compound and cannot be listed exhaustively here.



Radial shaft seal Simmerring® PPS



DESIGN GUIDELINE

- Please refer to the technical manual for design guidelines.

INSTALLATION GUIDELINE

- The prerequisite for perfect function of the seal is careful installation in accordance with the technical manual.

STORAGE ADVISE

- Storage temperature <25°C
- No direct heat sources
- No direct sunlight
- No condensation in the storage room
- No exposure to ozone or ionizing radiation
- Recommendations based on the revision of ISO 2230 dated 16.09.1992

The designation of this seal for sealing rotating shafts is radial shaft seal according to DIN/ISO. The name Simmerring® is a registered trademark of the Freudenberg company. The information contained herein is believed to be reliable, but no representations, warranties or guarantees of any kind are made as to its accuracy or suitability for any purpose. The information reproduced herein is based on laboratory testing and is not necessarily indicative of end product performance. Complete testing and performance of the end product is the responsibility of the user.
 © Freudenberg FST GmbH | www.fst.com